



Product Description

Our bespoke Aluminium capping/coping system is designed for each project ensuring that the unique site conditions and requirements are used to tailor the design. Our capping is suitable for any wall size and incorporates a secret fixing detail that allows the capping to be clipped into place. This clip arrangement ensures that the capping can expand and contract due to ambient temperature changes.

Key Facts about JB Capping

- ◆ Designed to fit all wall sizes
- ◆ Bespoke designs provided
- ◆ Hidden fixings
- ◆ Easy to install
- ◆ Minimal maintenance
- ◆ Site specific, strong ridged brackets manufactured for each project
- ◆ Curved profiles available
- ◆ Corners manufactured to match the building
- ◆ Huge range of colours available
- ◆ Minimum 25 year life
- ◆ Delivery throughout the UK

Fire Rating

The fire rating of JB PPC Aluminium Capping is A2-s1, d0.

Material

All capping is manufactured solely from aluminium (Grade 1050 H14) which is then powder coated. The thickness is either 2mm or 3mm and is dependent on the size required. The bracketry system is also manufactured from aluminium. To ensure a water tight seal, a long life high performance Butyl tape is used. This tape is strong, flexible and designed to accommodate movement.

Water Ingress

All joints are sealed using a long life high performance Butyl tape with a 25 year warranty. This strong high tack tape prevents water ingress while at the same time remaining flexible. All capping installed in accordance with our fitting instructions will have a 100% weathertight seal.

Contact us

Tel: **01384 563 510**
 Web site: **www.jbproducts.co.uk**
 Email: **info@jbproducts.co.uk**

Colour

Cappings are powder coated to any RAL/BS colour code using external architectural grade powder. Powder coating warranties can be provided on request.

Marine grade coatings are also available on request.

Structural

Structural calculations can be provided for the connection detail. The individual fixing arrangement is dependent on the structure and will alter project to project.

Maintenance

Aluminium capping is easy to maintain. It just needs an occasional wipe over with water and a mild detergent.

Handling and storage upon delivery

Capping will be delivered using our own fleet of vehicles wrapped securely on pallets. A fork lift will be required at the point of delivery to offload. The product will arrive with a low tack protective tape on the seen face that needs to be removed on completion of installation.

Installation

Aluminium capping can either be installed by our professional fitting teams or a competent fitter following our instructions and layout plans. Capping brackets are to be fixed to the parapet wall ensuring line and level. The capping then clips into place. Each joint has a powder coated joint bracket to ensure a high quality finish. All intermediate brackets are supplied self colour. All necessary butyl tapes are supplied with each delivery.

Disposal

As our capping is manufactured from aluminium it should be recycled at the end of its design life.

Further Information

For further information, advice and/or a quote please contact our specialist team on:

Tel: 01384 563 510

Email: info@jbproducts.co.uk

Manufactured by
JB Products
www.jbproducts.co.uk

 **Manufactured in Britain**

